

API Bellows Globe valve

ii




DN	L		H	W		Route of travel	Kv	Weight Kg	
	150LB	300LB		150LB	300LB	i ÷ H		150LB	300LB
15	108	452	191	120	140	6	4.2	3.7	4.3
20	117	178	191	120	140	6	7.4	4.4	4.8
25	127	203	197	140	140	8	12.0	5.1	6.3
32	140	216	200	140	160	8	19.0	7.5	7.8
40	165	229	218	160	180	13	30.0	8.8	10.3
50	203	267	220	180	180	13	47.0	12.2	12.6
65	216	292	238	180	200	16	77.0	16.1	19.0
80	241	318	250	200	250	20	120.0	21.4	25.0
100	292	356	300	250	300	25	188.0	33.0	35.0
125	356	400	350	300	350	32	288.0	51.0	56.0

150	406	444	350	300	350	40	410.0	69.0	74.0
200	495	559	450	400	450	50	725.0	105.0	160.0
250	622	622	520	520	520	65	1145.0	180.0	260.0
300	698	711	520	520	520	75	1635.0	265.0	370.0

Valve body, the valve cover	Valve pole	The $\delta$ shuts the piece	Seal completely the noodles	The ripples tube
GS-C25	2Cr13	2Cr13	2Cr13 , STL	SS304
1Cr 18Ni9Ti	1Cr 18Ni9Ti	1Cr 18Ni9Ti	1Cr18Ni 9 Tis, STL	SS304
CF3, CF8 CF3, CF8	SS316	SS316	304L,304 ,316 Ls, 316, STL	316

Mr. calls the pressure	1.6MPa	2.5MPa	4.0MPa
Hull body strength	2.4MPa	3.8MPa	6.0MPa



Seal completely to experiment	1.8MPa	2.8MPa	4.4MPa
Apply the temperature	-20350 jæs of j<		
Apply to lie the quality	Water, steam, Hot oil, oil article etc.		

Copyright: 2006 (C) China Zhejiang Teer Valve Co., Ltd.

Dong-ou Industrial Zone, Wenzhou, Zhejiang, China, 325100

Int'l trade: Tel:(86)577-57999777 67995111 67995115 67995116 Fax:57999888 Local sales: Tel:57989999 Fax:57989988

[HTTP://www.chinateer.com](http://www.chinateer.com) E-mail: [trade@chinateer.com](mailto:trade@chinateer.com)