



??

Bb Os & Y structure

Manufacture;êoDIN3356

Face to face;êoDIN3202

Butt-welding;êoDIN3239

Test;êoDIN3230

(nominal pressure)	1.6Mpa	2.5Mpa	4.0Mpa
(seal test)	1.8MPa	2.8MPa	4.4MPa
(shell)	2.4MPa	3.6MPa	6.0MPa
(suitable temperature)	300??		

PN1.6-6.4MPa

DN(mm)	(mm)							
	L	H	D	D <sub>0</sub>	D <sub>1</sub>	L <sub>1</sub>	a	°???
10	130	220	36	10	18.4	10	37.30??	120
15	130	245	36	15	22.5	10	37.30??	140
20	150	245	44	20	28.5	11	37.30??	160
25	160	265	48	25	34.5	12	37.30??	180
32	180	270	48	33	-	-	37.30??	200

40	200	285	55	39	-	-	37.30??	240
50	230	320	64	48	-	-	37.30??	300
65	290	365	82	65	-	-	37.30??	320
80	310	410	95	76	-	-	37.30??	360
100	350	430	117	98	-	-	37.30??	380
125	400	470	143	123	-	-	37.30??	400
150	480	500	167	148	-	-	37.30??	450
200	600	533	217	198	-	-	37.30??	500

Copyright: 2006 (C) China Zhejiang Teer Valve Co., Ltd.

Dong-ou Industrial Zone, Wenzhou, Zhejiang, China, 325100

Int'l trade: Tel:(86)577-57999777 67995111 67995115 67995116 Fax:57999888 Local sales: Tel:57989999 Fax:57989988

[HTTP://www.chinateer.com](http://www.chinateer.com) E-mail: [trade@chinateer.com](mailto:trade@chinateer.com)