



Characteristic: The double-decked corrugated pipe, the service is convenient, the dual seal, the position instruction
 Application situation: The power plant, the natural gas, the ammonia, the freezing are systematic, the hot oil system, the hot water
 The valve uses the standard: Valve design manufacture standard: DIN3356-82;
 Structural length standard: DIN3202;
 Flange standard: DIN2543-DIN2546;
 Valve experiment examination standard: DIN3230-75

Performance and outlook size

??

DN	L	H	W		Travelling schedule	Kv	kg		
			PN16 25	PN40	¿iÂh		PN16	PN25	PN40
15	130	191	120	140	6	4.2	3.7	4.3	4.3
20	150	191	120	140	6	7.4	4.4	4.8	4.8
25	160	197	140	140	8	12.0	5.1	6.3	6.3
32	180	200	140	160	8	19.0	7.5	7.8	7.8
40	200	218	160	180	13	30.0	8.8	10.3	10.3
50	230	220	180	180	13	47.0	12.2	12.6	12.6
65	290	238	180	200	16	77.0	16.1	19.0	19.0
80	310	257	200	250	20	120.0	21.4	25.0	25.0
100	350	340	250	300	25	188.0	33.0	35.0	35.0
125	400	360	300	350	32	288.0	51.0	56.0	56.0
150	480	390	300	350	40	410.0	69.0	74.0	74.0
200	600	530	400	450	50	725.0	105.0	144.0	160.0
250	730	665	520	520	65	1145.0	180.0	238.0	260.0
300	850	720	520	520	75	1635.0	265.0	339.0	370.0

??

Body?jéBonnet	stem	Opens shuts	Sealing Face	Bellows
GS-C25	2Cr13	2Cr13	2Cr13?jéSTL	SS304
1Cr18Ni9Ti	1Cr18Ni9Ti	1Cr18Ni9Ti	1Cr18Ni9Ti?jéSTL	SS304
CF3?jéCF8 CF3?jéCF8	SS316	SS316	304L?jé304?jé316L?jé316?jéSTL	316

Nominal Pressure	1.6MPa	2.5MPa	4.0MPa
Shell	2.4MPa	3.8MPa	6.0MPa
Seal Test	1.8MPa	2.8MPa	4.4MPa
Suitable Temperature			

??

??

??

??

??

Copyright: 2006 (C) China Zhejiang Teer Valve Co., Ltd.

Dong-ou Industrial Zone, Wenzhou, Zhejiang, China, 325100

Int'l trade: Tel:(86)577-57999777 67995111 67995115 67995116 Fax:57999888 Local sales: Tel:57989999 Fax:57989988

[HTTP://www.chinateer.com](http://www.chinateer.com) E-mail: trade@chinateer.com