



## Forged Steel Flange End Check Valve 900~1500Lb

### Standard Material Specifications

NO.	Part Name	CS to ASTM	AS to ASTM	SS to ASTM	
		Type A105	Type F22	Type F304(L)	Type F316(L)
1	Body	A105	A182 F22	A182 F304(L)	A182 F316(L)
2	Nameplate	SS			
3	Piston Disc	A276 420	A276 304	A276 304(L)	A276 316(L)
4	Bonnet	A105	A182 F22	A182 F304(L)	A182 F316(L)
5	Gasket	Corrugated SS + graphite			
6	Bolt	A193 B7	A193 B16	A182 B8(M)	A193 B8(M)
Suitable Medium		W.O.G.etc	W.O.G.etc	HNO <sub>3</sub> ,CH <sub>3</sub> OOH etc	
Suitable Temperature		-29 425	-29 550	-29 200	

**Note:** Other materials are available upon request.

## Dimensions (mm) and Weights (Kg)

NPS		1/2	3/4	1	1 1/4	1-1/2	2
L(RTJ)		216	229	254	279	305	371
L1(BW)		216	229	254	279	305	368
H		79	79	95	104	120	139
Weights	RTJ	8.5	10.5	15.7	20.8	27.2	33.0
	BW	6.4	8.0	13.2	17.8	24.2	29.7

Copyright: 2006 (C) China Zhejiang Teer Valve Co., Ltd.

Dong-ou Industrial Zone, Wenzhou, Zhejiang, China, 325100

Int'l trade: Tel:(86)577-57999777 67995111 67995115 67995116 Fax:57999888 Local sales: Tel:57989999

Fax:57989988

[HTTP://www.chinateer.com](http://www.chinateer.com) E-mail: [trade@chinateer.com](mailto:trade@chinateer.com)